



### Profitable in-house label printing

**Delivers on-demand, short-run colour label printing capability that drives new revenue streams**

### Versatile media handling

**Unrivalled media handling allows users to take on new creative ideas and complex jobs with ease**

### Bringing a new colour dimension to labels

**Fifth colour or CMYK+W option enables greater flexibility in label design**

### Robust water/chemical resistant printing

**Can produce waterproof labels that are robust and resistant to UV fading**

Printing Method:	Digital 5 LED Full-color Electrophotographic
Media Format:	Roll
Media Type:	Plain Paper, Film, Plain Paper Label, Glossy Paper Label, Film Label, Synthetic paper Label
Media Width:	29.64 - 130.0mm
Media Thickness:	0.076 - 0.25mm
Label Length:	12.7 - 1,320.8mm
Label Width:	25.4 - 125.76mm
Media Detection:	Gap, Black Mark (printed on back of liner)
Roll Outer Diameter:	Max. $\Phi$ 203.2mm ( $\Phi$ 8")
Core Inner Diameter:	$\Phi$ 76.2mm ( $\Phi$ 3")
Roll Wind Direction:	Face-out, Face-in
Print Width:	Max. 125.76mm
Minimum Print Margin:	Top: 2.12mm
Bottom:	2.12mm
Right:	2.12mm
Left:	2.12mm
Cuttable Media Length:	Min. 101.6mm
Print Resolution:	1200 x 1200 dpi, 600 x 600 dpi
Print Speed Max:	152.4mm/s (6ips)
Interface:	1000BASE-T/100BASE-TX/10BASE-T, USB 2.0 (High Speed)
Printer Language:	PCL 5c emulation, PCL 6 (XL) emulation, Adobe PostScript 3
Processor:	ARM CPU 1.2 GHz
Memory (Std./Max.):	2048 MB / 2048 MB
Hard Disk Drive:	250 GB
Font:	Adobe PostScript 136 fonts, PCL emulation 81 scalable fonts, 4 bitmap fonts
Media Sensors:	Position adjustable Transmission Gap Sensor Position adjustable Reflective Black Mark (printed on back of liner) Sensor
Auto Cutter:	Rotary blade Full cut
Dimensions(WxDxH):	1,040 x 477 x 441 mm
Weight:	61.0 kg - 62.0 kg
Power Consumption	Operating: Max. 1,200W / Ave. 740W
Idle:	27W
Power Save:	< 25.0W